


























New **SPC**
Generation
Flooring

WALL PANEL
COLLECTIONS
Technical Data Sheet

PRODUCT SPECIFICATION

DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
 MEDIUM	965 X 2600	MICRO BEVEL	WOOD- STONE	 Warranty[Year]
	Piece 1 pcs = 2.509 m ² = 20.07 kg	Palette [m ²] 60 x  = 163.085 m ² = 1.356.68 kg	Container[20'] 20 x  = 3.192.62 m ² = 25.504.94 kg	
 LONG	968 X 2800	MICRO BEVEL	WOOD- STONE	 Warranty[Year]
	Piece 6 x  = 2.230 m ² = 17.86 kg	Palette [m ²] 60 x  = 162.120 m ² = 1.346.96 kg	Container[20'] 20 x  = 3.214.94 m ² = 25.719.55 kg	

TECNICAL SPECIFICATION

	ICON	STANDARTS	SPECIFICATIONS
Surface treatment (UV)			Yes
Underlay		IXPE	1 mm
Total thickness		ISO24337	4 mm
Wear layer thickness		EN429	0.15 mm
Total weight		EN ISO 23997	9.5 kgs/sqm
Dimensional stability		TS EN ISO 23999	Class 34
Performance classification		23.34.43	
Residual indentation after static load		TS EN ISO 24343-1:2007	0.01 mm
Anti-slip resistance		EN 13893	DS
Electrostatic behavior		1815:2016	Anti static floor covering
Floor heating system		Suitable	Max.27 ⁰
Antibacterial		ISO 22196	Antibacterial
Pet-friendly			Pass
Phthalate analysis		Inhouse Methot	Phatalete free
Formaldehyde emissions		EN 717-1:2004	E1
Fire behavior		EN13501-1 EN 9239-1:2010	BFL-S1
Reaction to fire		EN 11925-2:2020	Bs-d0
Thermal resistance		EN 12667	0.296 W(m.K)
Matte Degree			2-4 ⁰
VOC emissions		FloorScore CE	Certified
Impact Sound Transmission		ASTM E492-09:2016 - ASTM E989-18	IIC=75dB
Airborne sound transmission loss		ASTM E413-16	R _w +C=75dB - STC = 73dB



WALL PANEL
COLLECTIONS